



8		7		6		5		4		3		2		1	
WEIGHT (LBS)		INDUCTANCE		LOSS (WATTS)											
19		0.17mH		119											
ECO No.		DESCRIPTION		REV BY		DATE									
M8321		DIMENSION CHANGE		JP		12/17/12									

- NOTES:
1. TERMINAL SCREW TIGHTENING TORQUE:
 - 6 - 4 (45) in-lbs MAX
 - 2 - 0 (50) in-lbs MAX
 2. WIRE RANGE: 6 - 0 AWG

THE COMPONENT, PART OR ASSEMBLY DESCRIBED IN THIS DOCUMENT MUST COMPLY WITH THE EUROPEAN UNION DIRECTIVE RoHS		MATERIAL		CONFIDENTIAL AND PROPRIETARY INFORMATION THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION OF MTE CORPORATION AND MAY NOT BE USED, COPIED OR DISCLOSED TO OTHERS EXCEPT WITH THE AUTHORIZED WRITTEN PERMISSION OF MTE CORPORATION	
CONTAINS <0.1% OF ANY SVHC BY WEIGHT PER REACH REGULATION				DESCRIPTION	
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES (MM) TOLERANCES ARE:		DRAWN JP		DATE 09/04/12	
ANGLES: ± 1 °		CHECKED TM		DATE 12/21/12	
1 PLACE .XX: ± .1 [2.5]		APPROVED TM		DATE 12/21/12	
2 PLACE .XX: ± .03 [0.76]				SIZE D	
3 PLACE .XXX: ± .010 [0.254]				DWG No. CD RLW-008301	
				REV 04	
				SCALE 4:4	
				SHEET 1 OF 1	

