APPROX. WEIGHT (LBS)
20

ECO No	DESCRIPTION	REV BY	DATE
M9002	UPDATE DRAWING TO CURRENT STANDARDS	MN	02/14/14



TOP VIEW



BOTTOM VIEW





DETAIL A
(2 PLACES)



FRONT VIEW



RIGHT SIDE VIEW



DETAIL B
CUSTOMER CONNECTION
DETAIL VIEW

NOTES:

1. FILTER REQUIRES CAPACITOR (CAP-338TP) (QTY. 1).
2. TERMINAL SCREW TIGHTENING TORQUE: 16 IN/LBS, MAX.
3. WIRE RANGE: 4-14 AWG.

THE COMPONENT, PART OR ASSEMBLY DESCRIBED IN THIS DOCUMENT MUST COMPLY WITH THE EU(EUROPEAN UNION) DIRECTIVE RoHS

CONTAINS <0.1% OF ANY SVHC BY WEIGHT PER REACH REGULATION

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES [MM] TOLERANCES ARE:

ANGLES: ± 1 °

1 PLACE .X: ± .1 [2.5]

2 PLACE .XX: ± .03 [0.76]

3 PLACE .XXX: ± .010 [0.254]

MTE
AN SL POWER ELECTRONICS COMPANY
N83 W13330 Leon Road
Menomonee Falls, WI 53051 USA
800.455-4683
262.253.8200

MATERIAL

DRAWN	DATE
JP	05/07/12
CHECKED	DATE
RH	02/20/14
APPROVED	DATE
RH	02/20/14

CONFIDENTIAL AND PROPRIETARY INFORMATION
THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION OF MTE CORPORATION AND MAY NOT BE USED, COPIED OR DISCLOSED TO OTHERS EXCEPT WITH THE AUTHORIZED WRITTEN PERMISSION OF MTE CORPORATION

DESCRIPTION

MATRIX AP 6A 480V 60HZ
OPEN PANEL

SIZE	DWG No.	REV
D	CD MAPP0006D	01

SCALE 1:1 SHEET 1 OF 1