



APPROX. WEIGHT  
(LBS)  
67

ECO No	DESCRIPTION	REV BY	DATE
M9058	UPDATE TO CURRENT DRAWING STANDARDS	MN	03/25/14

NOTES:

1. FILTER REQUIRES CAPACITOR (CAP-343TP) (QTY. 1).
2. TERMINAL SCREW TIGHTENING TORQUE: 16 IN/LBS, MAX.
3. WIRE RANGE: 4-14 AWG.

THE COMPONENT, PART OR ASSEMBLY DESCRIBED IN THIS DOCUMENT MUST COMPLY WITH THE EU(EUROPEAN UNION) DIRECTIVE RoHS		MATERIAL		CONFIDENTIAL AND PROPRIETARY INFORMATION THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION OF MTE CORPORATION AND MAY NOT BE USED, COPIED OR DISCLOSED TO OTHERS EXCEPT WITH THE AUTHORIZED WRITTEN PERMISSION OF MTE CORPORATION		
CONTAINS <0.1% OF ANY SVHC BY WEIGHT PER REACH REGULATION				DESCRIPTION		
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES [MM] TOLERANCES ARE:  ANGLES: ± 1 °  1 PLACE .X: ± .1 [2.5]  2 PLACE .XX: ± .03 [0.76]  3 PLACE .XXX: ± .010 [0.254]		<b>MTE</b> <small>AN BL POWER ELECTRONICS COMPANY</small>  N83 W13330 Leon Road Menomonee Falls, WI 53051 USA 800.455-4683 262.253.8200		MATRIX AP 34A 480V 60HZ OPEN PANEL		
DRAWN JP		DATE 05/10/12				
CHECKED RH		DATE 03/26/14				
APPROVED RH		DATE 03/26/14				
SIZE D		DWG No. CD MAPP0034D		REV 01		
SCALE 2:3				SHEET 1 OF 1		