



APPROX. WEIGHT
(LBS)
119

D

C

B

A

TOP VIEW

FRONT VIEW

BOTTOM VIEW

SIDE VIEW

CUSTOMER CONNECTION
DETAIL VIEW

- NOTES:**
1. TERMINAL WIRE RANGE: 4-14 AWG.
 2. TERMINAL SCREW TIGHTENING TORQUE: 16 IN·LBS.
 3. REFER TO USER MANUAL FOR COMPLETE INSTALLATION INSTRUCTIONS.
 4. FILTER INCLUDES: CAP-542SW (QTY. 2).

THE COMPONENT, PART OR ASSEMBLY DESCRIBED IN THIS DOCUMENT MUST COMPLY WITH THE EU (EUROPEAN UNION) DIRECTIVE RoHS2		MATERIAL		CONFIDENTIAL AND PROPRIETARY INFORMATION THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION OF MTE CORPORATION AND MAY NOT BE USED, COPIED OR DISCLOSED TO OTHERS EXCEPT WITH THE AUTHORIZED WRITTEN PERMISSION OF MTE CORPORATION		
CONTAINS <0.1% OF ANY SVHC BY WEIGHT PER REACH REGULATION				DESCRIPTION		
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES [MM] TOLERANCES ARE:				SWG 200A 208-240V 2-8kHz FILTER, OPEN PANEL		
ANGLES: ± 1 °				SIZE	DWG No.	REV
1 PLACE .X: ± .1 [2.5]				D	CD SWGM0200A	00
2 PLACE .XX: ± .03 [0.76]				SCALE	3:5	SHEET 1 OF 1
3 PLACE .XXX: ± .010 [0.254]						



N83 W13330 Leon Road
Menomonee Falls, WI 53051 USA
800.455-4683
262.253-8200

