



- NOTES:**
1. TERMINAL WIRE RANGE: 4-14 AWG.
  2. TERMINAL SCREW TIGHTENING TORQUE: 16 IN.LBS.
  3. REFER TO USER MANUAL FOR COMPLETE INSTALLATION INSTRUCTIONS.
  4. FILTER INCLUDES: CAP-541SW (QTY. 1) & CAP-538SW (QTY. 1).

THE COMPONENT, PART OR ASSEMBLY DESCRIBED IN THIS DOCUMENT MUST COMPLY WITH THE EU(EUROPEAN UNION) DIRECTIVE RoHS2		MATERIAL		CONFIDENTIAL AND PROPRIETARY INFORMATION THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION OF MTE CORPORATION AND MAY NOT BE USED, COPIED OR DISCLOSED TO OTHERS EXCEPT WITH THE AUTHORIZED WRITTEN PERMISSION OF MTE CORPORATION	
CONTAINS <0.1% OF ANY SVHC BY WEIGHT PER REACH REGULATION				DESCRIPTION	
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES [MM] TOLERANCES ARE:		DRAWN JD 07/23/19		SWG 250A 208-240V 2-8kHz FILTER, OPEN PANEL	
ANGLES: ± 1 °		CHECKED CH 11/08/19		SIZE D	
1 PLACE .X: ± .1 [2.5]		APPROVED PY 11/15/19		DWG No. CD SWGM0250A	
2 PLACE .XX: ± .03 [0.76]				REV 00	
3 PLACE .XXX: ± .010 [0.254]				SCALE 3:5	
				SHEET 1 OF 1	

